

012A291130 - IP 64 PAVIMENTI PINK

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 012A291130
Product name: IP 64 PAVIMENTI PINK
UFI : CS33-C09P-P00U-5YYR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Cleaner for floors and hard surfaces

Identified Uses	Industrial	Professional	Consumer
Cleaner for floors and hard surfaces	-	✓	✓
Uses Advised Against			
All other uses are not recommended			

1.3. Details of the supplier of the safety data sheet

Name: ALLEGRINI S.P.A.
Full address: Vicolo Salvo D'Acquisto, 2
District and Country: 24050 Grassobbio (BG) Italy
Tel.: +39 035 4242111
Fax: +39 035 526588
e-mail address of the competent person responsible for the Safety Data Sheet: msds@allegrini.com

1.4. Emergency telephone number

For urgent inquiries refer to: Allegrini SpA : Tel. +39 035 4242111 Mon - Fri 8.00 - 17.00 GMT +1

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

H319

Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319

Causes serious eye irritation.

012A291130 - IP 64 PAVIMENTI PINK

SECTION 2. Hazards identification ... / >>

Precautionary statements:

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280	Wear eye protection / face protection.
P337+P313	If eye irritation persists: Get medical advice / attention.
P264	Wash your hands thoroughly after use.

Ingredients (Regulation 648/2004)

Less than 5% Non-ionic surfactants
Perfumes
Citronellol, Geraniol, Hexyl Cinnamaldehyde, Linalool, Dimethyl Phenethyl Acetate, Hexamethylindanopyran, Tetramethyl acetyloctahydronaphthalenes
Preservation agents: (Benzyloxy)methanol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

A non -classified flammable product following the test test of combustion L.2, part III, section 32 of the United Nations Recommendations on the transport of dangerous goods, manual of evidence and criteria.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Ethanol		
INDEX 603-002-00-5	$6 \leq x < 7$	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC 200-578-6		Eye Irrit. 2 H319: $\geq$ 50%
CAS 64-17-5		
REACH Reg. 01-2119457610-43		
Alcohols, C12-15, branched and linear, ethoxylated		
INDEX 1 $\leq x < 1,5$		Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC 106232-83-1		LD50 Oral: >300 mg/kg
CAS 106232-83-1		
2-butoxyethanol		
INDEX 603-014-00-0	$1 \leq x < 1,5$	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0		LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h
CAS 111-76-2		
REACH Reg. 01-2119475108-36		
2-aminoethanol		
INDEX 603-030-00-8	$0,05 \leq x < 0,1$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B
EC 205-483-3		H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412
CAS 141-43-5		STOT SE 3 H335: $\geq$ 5%
		LD50 Oral: 1089 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
REACH Reg. 01-2119486455-28		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

ALLEGRI S.P.A.		Revision no.3 Revision date 05/12/2024 Printed on 05/12/2024 Page no. 4 / 15 Replaces revision:2 (Revision date 05/05/2023)	EN
012A291130 - IP 64 PAVIMENTI PINK			
SECTION 6. Accidental release measures ... / >>			
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.			
6.2. Environmental precautions			
The product must not penetrate into the sewer system or come into contact with surface water or ground water.			
6.3. Methods and material for containment and cleaning up			
Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.			
6.4. Reference to other sections			
Any information on personal protection and disposal is given in sections 8 and 13.			
SECTION 7. Handling and storage			
7.1. Precautions for safe handling			
Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.			
7.2. Conditions for safe storage, including any incompatibilities			
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.			
7.3. Specific end use(s)			
Information not available			
SECTION 8. Exposure controls/personal protection			
8.1. Control parameters			
Regulatory references:			
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)	
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci	
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58	
ESP	España	Límites de exposición profesional para agentes químicos en España 2023	
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]	
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021	
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»	
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről	
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)	
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81	
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)	

EPY 11.7.1 - SDS 1004.14

SECTION 8. Exposure controls/personal protection ... / >>

PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

Ethanol								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	1000						
TLV	CZE	1000	522	3000	1566			
AGW	DEU	380	200	1520	800			
MAK	DEU	380	200	1520	800			
VLA	ESP			1910	1000			
TLV	EST	1000	500	1900	1000			
VLEP	FRA	1900	1000	9500	5000			
TLV	GRC	1900	1000					
AK	HUN	1900		3800				
GVI/KGVI	HRV	1900	1000					
RV	LVA	1000						
NDS/NDSch	POL	1900						
TLV	ROU	1900	1000	9500	5000			
NGV/KGV	SWE	1000	500	1900 (C)	1000 (C)			
NPEL	SVK	960	500	1920	1000			
MV	SVN	960	500	1920	1000			
WEL	GBR	1920	1000					
TLV-ACGIH				1884	1000			
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,96	mg/l	
Normal value in marine water						0,79	mg/l	
Normal value for fresh water sediment						36	mg/kg	
Normal value for marine water sediment						2,9	mg/kg	
Normal value for water, intermittent release						2,75	mg/l	
Normal value of STP microorganisms						580	mg/l	
Normal value for the food chain (secondary poisoning)						0,72	mg/kg	
Normal value for the terrestrial compartment						0,63	mg/kg	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					1900			950
					mg/m3			mg/m3
Skin								343
								mg/kg/d

ALLEGRINI S.P.A.						Revision no.3 Revision date 05/12/2024 Printed on 05/12/2024 Page no. 6 / 15 Replaces revision:2 (Revision date 05/05/2023)			EN
012A291130 - IP 64 PAVIMENTI PINK									
SECTION 8. Exposure controls/personal protection ... / >>									
2-butoxyethanol									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
VLA	ESP	98	20	245	50	SKIN			
VLEP	ITA	98	20	246	50	SKIN			
MV	SVN	98	20	246	50	SKIN			
OEL	EU	98	20	246	50	SKIN			
TLV-ACGIH		97	20						
Predicted no-effect concentration - PNEC									
Normal value in fresh water						8,8	mg/l		
Normal value in marine water						0,88	mg/l		
Normal value for fresh water sediment						34,6	mg/kg		
Normal value for marine water sediment						3,46	mg/kg		
Normal value for water, intermittent release						26,4	mg/l		
Normal value of STP microorganisms						463	mg/l		
Normal value for the terrestrial compartment						2,33	mg/kg		
Health - Derived no-effect level - DNEL / DMEL									
Route of exposure	Effects on consumers				Effects on workers				
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic	
	local	systemic	local	systemic	local	systemic	local	systemic	
Oral		26,7		6,3					
		mg/kg bw/d		mg/kg bw/d					
Inhalation	147	426		59	246	1091		98	
	mg/m3	mg/m3		mg/m3	mg/m3	mg/m3		mg/m3	

EPY 11.7.1 - SDS 1004.14

012A291130 - IP 64 PAVIMENTI PINK

SECTION 8. Exposure controls/personal protection ... / >>

2-aminoethanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	2,5	1	7,6	3	SKIN
TLV	CZE	2,5	0,985	7,5	2,955	
AGW	DEU	0,5	0,2	0,5	0,2	SKIN
MAK	DEU	0,51	0,2	0,51	0,2	
VLA	ESP	2,5	1	7,5	3	SKIN
TLV	EST	2,5	1	7,6	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
TLV	GRC	2,5	1	7,6	3	
AK	HUN	2,5		7,6		SKIN
GVI/KGVI	HRV	2,5	1	7,6	3	SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
RV	LVA	0,5	0,2	7,6	3	SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
NDS/NDSch	POL	2,5		7,5		SKIN
TLV	ROU	2,5	1	7,6	3	SKIN
NGV/KGV	SWE	2,5	1	7,5	3	SKIN
NPEL	SVK	2,5	1	7,6	3	SKIN
MV	SVN	2,5	1	7,6	3	SKIN
WEL	GBR	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN
TLV-ACGIH		7,5	3	15	6	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,07	mg/l
Normal value in marine water	0,007	mg/l
Normal value for fresh water sediment	0,357	mg/kg
Normal value for marine water sediment	0,0357	mg/kg
Normal value for water, intermittent release	0,028	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	1,29	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,5 mg/kg				
Inhalation				0,18 mg/m3				0,51 mg/m3
Skin				1,5 mg/kg				3 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the

012A291130 - IP 64 PAVIMENTI PINK

SECTION 8. Exposure controls/personal protection ... / >>

threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	pink	
Odour	floral	
Melting point / freezing point	not available	
Initial boiling point	> 35 °C	
Flammability	not flammable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	40 °C	Remark: Product not classified as flammable following the sustained combustion test L.2, part III, section 32 of the United Nations Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	8.5-9.5	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,99 g/cm ³	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-butoxyethanol

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

012A291130 - IP 64 PAVIMENTI PINK

SECTION 10. Stability and reactivity ... / >>

The vapours may also form explosive mixtures with the air.

Ethanol

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

2-butoxyethanol

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

2-aminoethanol

May react dangerously with: acrylonitrile,chloroepoxypropane,chlorosulphuric acid,hydrogen chloride,iron-sulphur compounds,acetic acid,acetic anhydride,mesityl oxide,nitric acid,sulphuric acid,strong acids,vinyl acetate,cellulose nitrate.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethanol

Avoid exposure to: sources of heat,naked flames.

2-butoxyethanol

Avoid exposure to: sources of heat,naked flames.

2-aminoethanol

Avoid exposure to: air,sources of heat.

10.5. Incompatible materials

2-butoxyethanol

Avoid contact with: strong oxidising agents,strong acids.

2-aminoethanol

Incompatible with: iron,strong acids,strong oxidants.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-butoxyethanol

May develop: hydrogen.

2-aminoethanol

May develop: nitric oxide,carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

>2000 mg/kg

ATE (Dermal) of the mixture:

Not classified (no significant component)

012A291130 - IP 64 PAVIMENTI PINK

SECTION 11. Toxicological information ... / >>

Alcohols, C12-15, branched and linear, ethoxylated LD50 (Oral):	> 300 mg/kg Rat
Ethanol LD50 (Oral):	> 6,2 mg/kg Rat
LC50 (Inhalation vapours):	> 50 mg/l/4h Rat
2-butoxyethanol LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat
2-aminoethanol LD50 (Dermal):	2504 mg/kg (BW/d) Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	1089 mg/kg (bw/d) Rat
LC50 (Inhalation vapours):	> 1,3 mg/l/6h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Route of exposure

2-aminoethanol
NOEL (C) oral: 300 mg / kg bw / d (Rat); NOAEC inhalation: 10 mg / m3 (Rat)

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

012A291130 - IP 64 PAVIMENTI PINK

SECTION 12. Ecological information ... / >>

12.1. Toxicity

Alcohols, C12-15, branched and linear, ethoxylated	
Chronic NOEC for Fish	> 0,1 mg/l Carassius Auratus
Chronic NOEC for Crustacea	> 0,1 mg/l Daphnia
Chronic NOEC for Algae / Aquatic Plants	> 0,1 mg/l
Ethanol	
LC50 - for Fish	> 13000 mg/l/96h salmo gairdneri
EC50 - for Crustacea	> 12300 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants	> 275 mg/l/72h chlorella vulgaris
2-butoxyethanol	
LC50 - for Fish	1474 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1550 mg/l/48h Daphnia magna
Chronic NOEC for Fish	> 100 mg/l Brachydanio rerio
2-aminoethanol	
LC50 - for Fish	349 mg/l/96h Cyprinus carpio
EC50 - for Crustacea	65 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	2,8 mg/l/72h Salenastrum capricornutum
Chronic NOEC for Fish	1,24 mg/l (41d) Oryzias latipes
Chronic NOEC for Crustacea	0,85 mg/l (21d) Daphnia magna

12.2. Persistence and degradability

Alcohols, C12-15, branched and linear, ethoxylated
Biodegradability: 70% (28d) (OECD 301F)

2-aminoethanol
Biodegradability: > 90% (21d)

Alcohols, C12-15, branched and linear, ethoxylated
Rapidly degradable

Ethanol
Rapidly degradable

2-butoxyethanol
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-aminoethanol
Solubility in water > 1000 g/l
Rapidly degradable >90% (21d)

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

ALLEGRINI S.P.A. 012A291130 - IP 64 PAVIMENTI PINK	Revision no.3 Revision date 05/12/2024 Printed on 05/12/2024 Page no. 12 / 15 Replaces revision:2 (Revision date 05/05/2023) EN
Information not available	
SECTION 13. Disposal considerations	
13.1. Waste treatment methods Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.	
SECTION 14. Transport information	
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations. 14.1. UN number or ID number not applicable A non -classified flammable product following the test test of combustion L.2, part III, section 32 of the United Nations Recommendations on the transport of dangerous goods, manual of evidence and criteria. 14.2. UN proper shipping name not applicable 14.3. Transport hazard class(es) not applicable 14.4. Packing group not applicable 14.5. Environmental hazards not applicable 14.6. Special precautions for user not applicable 14.7. Maritime transport in bulk according to IMO instruments Information not relevant	
SECTION 15. Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Seveso Category - Directive 2012/18/EU: None Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product Point 3 - 40 Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.	

012A291130 - IP 64 PAVIMENTI PINK

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

2-aminoethanol

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

012A291130 - IP 64 PAVIMENTI PINK

SECTION 16. Other information ... / >>

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

SECTION 16. Other information ... / >>

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 16.