

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 012A291271
Product name: M 15 PLUS LAVATESSUTI PROFUMATO
UFI : YMN2-U0E6-5006-0NU3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Carpet cleaner

Identified Uses	Industrial	Professional	Consumer
Cleaner for carpets and rugs	-	✓	-
Uses Advised Against			
Do not use for purposes other than those indicated			

1.3. Details of the supplier of the safety data sheet

Name: ALLEGRINI S.P.A.
Full address: Vicolo Salvo D'Acquisto, 2
District and Country: 24050 Grassobbio (BG) Italy
Tel.: +39 035 4242111
Fax: +39 035 526588
e-mail address of the competent person responsible for the Safety Data Sheet: msds@allegrini.com

1.4. Emergency telephone number

For urgent inquiries refer to: Allegrini SpA : Tel. +39 035 4242111 Mon - Fri 8.00 - 17.00 GMT +1

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:
Serious eye damage, category 1 H318 Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:
H318 Causes serious eye damage.

ALLEGRINI S.P.A.

Revision no.1
Revision date 09/05/2024
New emission
Printed on 13/05/2024
Page no. 2 / 17

EN

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 2. Hazards identification

... / >>

Precautionary statements:

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P280

Wear eye protection / face protection.

P310

Immediately call a POISON CENTER/doctor.

Contains:

Hexyl D-glucoside
Alcohols, C8-10, ethoxylated propoxylated
Tetrasodium ethylene diamine tetraacetate

Ingredients (Regulation 648/2004)

Less than 5%

Phosphates, Soap, EDTA

5% or over but less than 15%

Non-ionic surfactants

Perfumes
Citronellol, Geraniol, Hexyl Cinnamaldehyde, Hexamethylindanopyran
Preservation agents: (Benzyloxy)methanol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hexyl D-glucoside INDEX EC 259-217-6 CAS 54549-24-5 REACH Reg. 01-2119492545-29	3,5 ≤ x < 4	Eye Dam. 1 H318
2-butoxyethanol INDEX EC 203-905-0 CAS 111-76-2 REACH Reg. 01-2119475108-36	3 ≤ x < 3,5	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315 LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h
Tetrapotassium pyrophosphate INDEX EC 230-785-7 CAS 7320-34-5 REACH Reg. 01-2119489369-18	2,5 ≤ x < 3	Eye Irrit. 2 H319
Alcohols, C8-10, ethoxylated propoxylated INDEX EC 614-633-0 CAS 68603-25-8	1,5 ≤ x < 2	Eye Dam. 1 H318
Ethanol INDEX EC 200-578-6 CAS 64-17-5 REACH Reg. 01-2119457610-43	1 ≤ x < 1,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319 Eye Irrit. 2 H319: ≥ 50%
Tetrasodium ethylene diamine tetraacetate INDEX EC 200-573-9 CAS 64-02-8 REACH Reg. 01-2119486762-27	1 ≤ x < 1,5	Acute Tox. 4 H302, Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318 ATE Oral: 500 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l

EPY 11.7.1 - SDS 1004.14

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 3. Composition/information on ingredients ... / >>

2-aminoethanol

INDEX 603-030-00-8 $0,5 \leq x < 0,6$

EC 205-483-3

CAS 141-43-5

REACH Reg. 01-2119486455-28

Methyl ethyl ketone

INDEX 606-002-00-3 $0 < x < 0,05$

EC 201-159-0

CAS 78-93-3

REACH Reg. 01-2119457290-43

Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412
STOT SE 3 H335: $\geq 5\%$
LD50 Oral: 1089 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER/doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

ALLEGRINI S.P.A. 012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO		Revision no.1 Revision date 09/05/2024 New emission Printed on 13/05/2024 Page no. 4 / 17 EN
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).		
SECTION 6. Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
Block the leakage if there is no hazard. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.		
6.2. Environmental precautions		
The product must not penetrate into the sewer system or come into contact with surface water or ground water.		
6.3. Methods and material for containment and cleaning up		
Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.		
6.4. Reference to other sections		
Any information on personal protection and disposal is given in sections 8 and 13.		
SECTION 7. Handling and storage		
7.1. Precautions for safe handling		
Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.		
7.2. Conditions for safe storage, including any incompatibilities		
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.		
7.3. Specific end use(s)		
Information not available		
SECTION 8. Exposure controls/personal protection		
8.1. Control parameters		
Regulatory references:		
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse

ALLEGRINI S.P.A.

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

Revision no.1

Revision date 09/05/2024

New emission

Printed on 13/05/2024

Page no. 5 / 17

EN

SECTION 8. Exposure controls/personal protection ... / >>

FRA	France	nőuded ning töökeskkonna keemiliste ohutegurite piinormid [RT I, 21.12.2022, 14] Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

Tetrasodium ethylene diamine tetraacetate

Predicted no-effect concentration - PNEC

Normal value in fresh water	2,2	mg/l
Normal value in marine water	0,22	mg/l
Normal value for water, intermittent release	1,2	mg/l
Normal value of STP microorganisms	43	mg/l
Normal value for the terrestrial compartment	0,72	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 mg/kg				
Inhalation	1,2 mg/m3			0,6 mg/m3	3 mg/m3			1,5 mg/m3

CEPY 11.7.1 - SDS 1004.14

SECTION 8. Exposure controls/personal protection ... / >>

Hexyl D-glucoside								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,176	mg/l			
Normal value in marine water				0,018	mg/l			
Normal value for fresh water sediment				0,722	mg/kg			
Normal value for marine water sediment				0,072	mg/kg			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				0,654	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	
Oral				35,7 mg/kg bw/d				
Inhalation				124 mg/m3				420 mg/m3
Skin				357000 mg/kg bw/d				595000 mg/kg bw/d

Ethanol								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	1000						
TLV	CZE	1000	522	3000	1566			
AGW	DEU	380	200	1520	800			
MAK	DEU	380	200	1520	800			
VLA	ESP			1910	1000			
TLV	EST	1000	500	1900	1000			
VLEP	FRA	1900	1000	9500	5000			
TLV	GRC	1900	1000					
AK	HUN	1900		3800				
GVI/KGVI	HRV	1900	1000					
RV	LVA	1000						
NDS/NDSch	POL	1900						
TLV	ROU	1900	1000	9500	5000			
NGV/KGV	SWE	1000	500	1900 (C)	1000 (C)			
NPEL	SVK	960	500	1920	1000			
MV	SVN	960	500	1920	1000			
WEL	GBR	1920	1000					
TLV-ACGIH				1884	1000			
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,96	mg/l	
Normal value in marine water						0,79	mg/l	
Normal value for fresh water sediment						36	mg/kg	
Normal value for marine water sediment						2,9	mg/kg	
Normal value for water, intermittent release						2,75	mg/l	
Normal value of STP microorganisms						580	mg/l	
Normal value for the food chain (secondary poisoning)						0,72	mg/kg	
Normal value for the terrestrial compartment						0,63	mg/kg	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Chronic	Chronic	Effects on workers		
	Acute	Acute				Acute	Acute	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					1900			950
					mg/m3			mg/m3
Skin								343
								mg/kg/d

ALLEGRINI S.P.A.

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

Revision no.1
Revision date 09/05/2024
New emission
Printed on 13/05/2024
Page no. 7 / 17

EN

SECTION 8. Exposure controls/personal protection ... / >>

2-butoxyethanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	98	20	245	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
MV	SVN	98	20	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value for water, intermittent release	26,4	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the terrestrial compartment	2,33	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		26,7 mg/kg bw/d		6,3 mg/kg bw/d				
Inhalation	147 mg/m3	426 mg/m3		59 mg/m3	246 mg/m3	1091 mg/m3		98 mg/m3

EPY 11.7.1 - SDS 1004.14

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 8. Exposure controls/personal protection ... / >>

2-aminoethanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	2,5	1	7,6	3	SKIN
TLV	CZE	2,5	0,985	7,5	2,955	
AGW	DEU	0,5	0,2	0,5	0,2	SKIN
MAK	DEU	0,51	0,2	0,51	0,2	
VLA	ESP	2,5	1	7,5	3	SKIN
TLV	EST	2,5	1	7,6	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
TLV	GRC	2,5	1	7,6	3	
AK	HUN	2,5		7,6		SKIN
GVI/KGVI	HRV	2,5	1	7,6	3	SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
RV	LVA	0,5	0,2	7,6	3	SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
NDS/NDSch	POL	2,5		7,5		SKIN
TLV	ROU	2,5	1	7,6	3	SKIN
NGV/KGV	SWE	2,5	1	7,5	3	SKIN
NPEL	SVK	2,5	1	7,6	3	SKIN
MV	SVN	2,5	1	7,6	3	SKIN
WEL	GBR	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN
TLV-ACGIH		7,5	3	15	6	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,07	mg/l
Normal value in marine water	0,007	mg/l
Normal value for fresh water sediment	0,357	mg/kg
Normal value for marine water sediment	0,0357	mg/kg
Normal value for water, intermittent release	0,028	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	1,29	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				1,5				
				mg/kg				
Inhalation				0,18				0,51
				mg/m3				mg/m3
Skin				1,5				3
				mg/kg				mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

Methyl ethyl ketone

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
TLV	BGR	590		885		
TLV	CZE	600	200,4	900	300,6	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
VLA	ESP	600	200	900	300	
TLV	EST	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600		900		SKIN
GVI/KGVI	HRV	600	200	900	300	
VLEP	ITA	600	200	900	300	
RV	LVA	200	67	900	300	
VLE	PRT	600	200	900	300	
NDS/NDSch	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
NGV/KGV	SWE	150	50	900	300	
NPEL	SVK	600	200	900	300	
MV	SVN	600	200	900	300	SKIN
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

Tetrapotassium pyrophosphate

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
Inhalation	local	systemic	local	systemic	local	systemic	local	systemic
				4,35 mg/m3				17,63 mg/m3

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellow	
Odour	fragrant	
Melting point / freezing point	not available	
Initial boiling point	100 °C	
Flammability	not flammable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	11-11.4	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1.04-1.06 g/cm3	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-butoxyethanol

Decomposes under the effect of heat.

Methyl ethyl ketone

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Ethanol

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

2-butoxyethanol

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

2-aminoethanol

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 10. Stability and reactivity ... / >>

Methyl ethyl ketone

May form peroxides with: air,light,strong oxidising agents.Risk of explosion on contact with: hydrogen peroxide,nitric acid,sulphuric acid.May react dangerously with: oxidising agents,trichloromethane,alkalis.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethanol

Avoid exposure to: sources of heat,naked flames.

2-butoxyethanol

Avoid exposure to: sources of heat,naked flames.

2-aminoethanol

Avoid exposure to: air,sources of heat.

Methyl ethyl ketone

Avoid exposure to: sources of heat.

10.5. Incompatible materials

2-butoxyethanol

Avoid contact with: strong oxidising agents,strong acids.

2-aminoethanol

Incompatible with: iron,strong acids,strong oxidants.

Methyl ethyl ketone

Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform.

Tetrapotassium pyrophosphate

Avoid contact with: strong acids.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-butoxyethanol

May develop: hydrogen.

2-aminoethanol

May develop: nitric oxide,carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:

> 5 mg/l

ATE (Inhalation - vapours) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

>2000 mg/kg

ATE (Dermal) of the mixture:

Not classified (no significant component)

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 11. Toxicological information ... / >>

Tetrasodium ethylene diamine tetraacetate	
LD50 (Oral):	1780 mg/kg Rat
ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation vapours):	> 1 mg/l/4h Rat
ATE (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)
Hexyl D-glucoside	
LD50 (Dermal):	> 2000 mg/kg Rabbit
LD50 (Oral):	> 2000 mg/kg Rat
Ethanol	
LD50 (Oral):	> 6,2 mg/kg Rat
LC50 (Inhalation vapours):	> 50 mg/l/4h Rat
2-butoxyethanol	
LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat
2-aminoethanol	
LD50 (Dermal):	2504 mg/kg (BW/d) Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	1089 mg/kg (bw/d) Rat
LC50 (Inhalation vapours):	> 1,3 mg/l/6h Rat
Methyl ethyl ketone	
LD50 (Dermal):	6480 mg/kg Rabbit
LD50 (Oral):	2737 mg/kg Rat
LC50 (Inhalation vapours):	23,5 mg/l/8h Rat
Tetrapotassium pyrophosphate	
LD50 (Oral):	> 2000 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Tetrasodium ethylene diamine tetraacetate
NOAEL: F1: > 250 mg/kg (Rat)

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 11. Toxicological information ... / >>

Route of exposure

2-aminoethanol
NOEL (C) oral: 300 mg / kg bw / d (Rat); NOAEC inhalation: 10 mg / m3 (Rat)

Tetrapotassium pyrophosphate
Oral NOAEL: 500 mg/kg (rat) (90d)

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Hexyl D-glucoside
NOEC algae: > 100 mg/l (72h)
NOEC daphnia: > 1-10 mg/l (21d) Daphnia magna

Tetrapotassium pyrophosphate
EC50 activated sludge: 1000 mg/l (3h)

Tetrasodium ethylene diamine tetraacetate
LC50 - for Fish > 100 mg/l/96h
EC50 - for Crustacea 140 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 25,7 mg/l (35d)
Chronic NOEC for Crustacea > 25 mg/l (21d)

Hexyl D-glucoside
LC50 - for Fish > 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea > 100 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Scenedesmus quadricauda

Ethanol
LC50 - for Fish > 13000 mg/l/96h salmo gairdneri
EC50 - for Crustacea > 12300 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants > 275 mg/l/72h chlorella vulgaris

2-butoxyethanol
LC50 - for Fish 1474 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea 1550 mg/l/48h Daphnia magna
Chronic NOEC for Fish > 100 mg/l Brachydanio rerio

2-aminoethanol
LC50 - for Fish 349 mg/l/96h Cyprinus carpio
EC50 - for Crustacea 65 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 2,8 mg/l/72h Salinastrum capricornutum
Chronic NOEC for Fish 1,24 mg/l (41d) Oryzias latipes
Chronic NOEC for Crustacea 0,85 mg/l (21d) Daphnia magna

Tetrapotassium pyrophosphate
LC50 - for Fish > 100 mg/l/96h
EC50 - for Crustacea > 100 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

12.2. Persistence and degradability

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 12. Ecological information ... / >>

2-aminoethanol

Biodegradability: > 90% (21d)

Tetrasodium ethylene diamine tetraacetate

NOT rapidly degradable

Hexyl D-glucoside

Rapidly degradable

Ethanol

Rapidly degradable

2-butoxyethanol

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

2-aminoethanol

Solubility in water

> 1000 g/l

Rapidly degradable

>90% (21d)

Methyl ethyl ketone

Solubility in water

> 10000 mg/l

Rapidly degradable

Tetrapotassium pyrophosphate

Solubility in water

> 10000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

Methyl ethyl ketone

Partition coefficient: n-octanol/water

0,3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 14. Transport information ... / >>

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
None

Substances subject to the Rotterdam Convention:
None

Substances subject to the Stockholm Convention:
None

Healthcare controls
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 15. Regulatory information ... / >>

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances
2-aminoethanol

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit

012A291271 - M 15 PLUS LAVATESSUTI PROFUMATO

SECTION 16. Other information ... / >>

- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

09.