

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

1 / 10

In conformity to Regulation (EU) 2015/830

SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : STOFFINET spray
Trades code : 016SNET0012

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent for carpets and moquettes

Sectors of use:

Private households (= general public = consumers)[SU21], Professional use[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Allegrini S.p.A.
Vicolo Salvo d'Acquisto, 2
24050 Grassobbio (BG) Italy
Tel. +39 035 4242111
e-mail: msds@allegrini.com

Produced by
Allegrini S.p.A.

1.4. Emergency telephone number

Allegrini SpA : Tel. +39 035 4242111 Lun. - Ven. 8.00 - 17.00 GMT +1

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS02, GHS07

Hazard Class and Category Code(s):
Flam. Aerosol 1, Eye Irrit. 2

Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.

Aerosol that ignites easily even at low temperatures, fire risk
If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.
The repeated inhalation of vapors can cause drowsiness and giddiness.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.
The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):



STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

2 / 10

In conformity to Regulation (EU) 2015/830

GHS02, GHS07 - Danger

Hazard statement Code(s):

- H222 - Extremely flammable aerosol.
- H229 - Pressurised container: May burst if heated.
- H319 - Causes serious eye irritation.

Supplemental Hazard statement Code(s):

unavailable

Precautionary statements:

General

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.

Prevention

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Do not pierce or burn, even after use.

Response

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains (Reg.EC 648/2004): > 5% < 15% aliphatic hydrocarbons, < 5% perfumes, anionic surfactants, phosphates

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

Packaging to be fitted with a tactile warning

SECTION3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements.

NOTE: SUBSTANCES MARKED WITH (*) HAVE SPECIFIC LIMITS

Hydrocarbons C3-4 contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Hydrocarbons C3-4	> 5 <= 10%	Flam. Gas 1, H220; Liq. Gas, H280	n.d.	68476-40-4	270-681-9	01-2119486 557-22
Sodium Lauryl Sarcosinate	>= 1 <= 5%	Skin Irrit. 2, H315; Eye Dam. 1, H318; Acute Tox. 2, H330	n.d.	137-16-6	205-281-5	01-2119527 780-39
Ethanol (*)	> 1 <= 5%	Flam. Liq. 2, H225; Eye Irrit. 2, H319	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43
Ammonium Hydroxide (*)	> 0,1 <= 1%	Skin Corr. 1B, H314; STOT SE 3, H335;	007-001-01-2	1336-21-6	215-647-6	01-2119488 876-14

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

3 / 10

In conformity to Regulation (EU) 2015/830

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
		Aquatic Acute 1, H400; Aquatic Chronic 2, H411				

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek for medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Ingestion:

Rinse mouth with water. It's possible to give activated charcoal in water or liquid paraffin medicine.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:

Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

4 / 10

In conformity to Regulation (EU) 2015/830

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1 For non-emergency personnel:**

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Eliminate all unattended flames and possible sources of ignition. Do not smoke.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up**6.3.1 For containment:**

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors

Do not smoke at work

While working do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

5 / 10

In conformity to Regulation (EU) 2015/830

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Private households (= general public = consumers):
Handle with care. Keep container tightly closed.

Professional use:
Handle with care. Store in a ventilated area and away from heat. Keep container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

Hydrocarbons C3-4:
TLV-TWA : 1000 ppm

Ammonium Hydroxide (*):
TLV/STEL (EC) : 35 ppm , 24 mg/m3
TLV/TWA (EC) : 25 ppm , 17 mg/m3
DNEL
Systemic effects Long term Workers inhalation = 14 (mg/m3)
Systemic effects Short term Workers inhalation = 36 (mg/m3)
Systemic effects Short term Workers dermal = 6,8 (mg/kg bw/day)
PNEC
Sweet water = 0,001 (mg/l)
Sea water = 0,001 (mg/l)
intermittent emissions = 0,089 (mg/l)

8.2. Exposure controls

Appropriate engineering controls:
Private households (= general public = consumers):
None.

Professional use:
None.

Individual protection measures:

(a) Eye / face protection
When handling the pure product use safety glasses (spectacles cage) (EN 166).

(b) Skin protection

(i) Hands protection
Not needed for normal use.

(ii) Other
Avoid direct contact with the skin
Better to use cotton antistatic clothing

(c) Respiratory protection
Work in a sufficiently ventilated to avoid inhaling the product.

(d) Thermal hazards
No hazard to report



STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

6 / 10

In conformity to Regulation (EU) 2015/830

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	spray can	
Odour	scented	
Odour threshold	not determined	
pH	10.5 (active)	
Melting point/freezing point	< 0 °C	
Initial boiling point and boiling range	approx. 100 °C (active)	
Flash point	aerosols classified extremely flammable	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	inflammabile	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	1.005 g/ml (active)	
Solubility	in water	
Water solubility	complete	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	undefined	
Oxidising properties	non-oxidizing	
Container volume	520 ml	
Product volume	400 ml	
Pressure to 20°C	approx. 4 atm	
Deformation pressure	approx. 15 atm	
Burst pressure of the container	> 15 atm	
Flash point of liquid phase	non flammable	
Propellant inflammability	< -80 °C	

9.2. Other information

No data available.

SECTION10. Stability and reactivity

10.1. Reactivity

No reactivity hazard.

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

7 / 10

In conformity to Regulation (EU) 2015/830

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 ° C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

It does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = 237.228,3 mg/kg

ATE(mix) dermal = 271.739,1 mg/kg

ATE(mix) inhal = n.d.

(a) acute toxicity: based on available data, the classification criteria are not satisfied.

(b) skin corrosion/irritation based on available data, the classification criteria are not satisfied.

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

(d) respiratory or skin sensitization: based on available data, the classification criteria are not satisfied.

(e) germ cell mutagenicity: based on available data, the classification criteria are not satisfied.

(f) carcinogenicity: based on available data, the classification criteria are not satisfied.

(g) reproductive toxicity: based on available data, the classification criteria are not satisfied.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not satisfied.

(i) specific target organ toxicity (STOT) repeated exposure Sodium Lauryl Sarcosinate: NOAEL oral (rat): 30 mg/kg (90d)

(j) aspiration hazard: based on available data, the classification criteria are not satisfied.

Related to contained substances:

Sodium Lauryl Sarcosinate:

LD50 (rat) Oral (mg/kg body weight) = 5000

Ethanol (*):

LD50 (rat) Oral (mg/kg body weight) = 10470

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 124,7

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

8 / 10

In conformity to Regulation (EU) 2015/830

Ammonium Hydroxide (*):
NOAEL oral (mammal) : 68 mg/kg (4 weeks)
LCLo inhalation (man) : 30.000 ppm (5min)
LCLo inhalation (rat) : 2.000 ppm (4h)
LD50 (rat) Oral (mg/kg body weight) = 350

SECTION 12. Ecological information**12.1. Toxicity**

Related to contained substances:

Sodium Lauryl Sarcosinate:
LC50 (fish) : 107 mg/l (96h)
EC50 (daphnia) : 29.7 mg/l (48h)
EC50 (algae) : 79 mg/l (72h)
EC50 (microorganisms) : 1000 mg/l (3h)

Ethanol (*):
LD50 (fish): > 12000 mg/l (96h)
EC50 (daphnia): > 10000 mg/l (48h)
EC50 (algae): > 200 mg/l (72h)

Ammonium Hydroxide (*):
LC50 (fish) : 0.89 mg/l (96h)
EC50 (daphnia) : 101 mg/l (48h)
NOEC (daphnia) : 0.79 mg/l (96h)

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

Hydrocarbons C3-4:
ODP = 0

Sodium Lauryl Sarcosinate:
Degradability : 82% (28d) (ISO Guideline No 14593)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

Surfactants contained in this formula are in compliance with biodegradability parameters established by regulation EC 648/2004 related to detergents.

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

9 / 10

In conformity to Regulation (EU) 2015/830

All supporting information are on hand of authorities of member countries and will be supplied to above mentioned authorities according to their explicit request or following producer's request.

SECTION13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Operate according to local or national regulations

SECTION14. Transport information

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 1950

If subject to the following characteristics is ADR exempt:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

ADR/RID/IMDG: AEROSOL flammable

ICAO-IATA: AEROSOL flammable

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 2

ADR/RID/IMDG/ICAO-IATA: Label : 2.1

ADR: Tunnel restriction code : D

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS : F-D, S-U

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: --

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous

IMDG: Marine polluting agent : Not

14.6. Special precautions for user

Transport must be executed through vehicles authorized for transport of dangerous goods, according to regulations of current edition of agreement A.D.R. and to national dispositions applicable.

Transport must be done in original packaging and, however, they must be made of materials unassailable by the content and not able to create dangerous reactions. Staff assigned to loading and unloading of dangerous goods must be well educated to hazards of the product and procedures to be adopted in case of emergency situation.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

D.Lgs. 3/2/1997 n. 52 (Classification, packaging and labelling of dangerous substances). D.Lgs 14/3/2003 n. 65

STOFFINET spray

Issued on 07/13/2012 - Rel. # 5 on 07/18/2017

10 / 10

In conformity to Regulation (EU) 2015/830

(Classification, packaging and labelling of dangerous preparations). D.Lgs. 2/2/2002 n. 25 (Risks derived from chemical agents during work). D.M. Labour 26/02/2004 (Limits for professional exposure). D.M. 03/04/2007 (Fulfillment of EU regulation 2006/8). EU Regulation n. 1907/2006 (REACH), Regulation (CE) n. 1272/2008 (CLP). Regulation (CE) n.790/2009.D.Lgs. 21/09/2005 n. 238 (Direttiva Seveso Ter).

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information**16.1. Other information**

Points modified compared to previous release: 1.2. Relevant identified uses of the substance or mixture and uses advised against, 1.3. Details of the supplier of the safety data sheet, 1.4. Emergency telephone number, 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 4.2. Most important symptoms and effects, both acute and delayed, 4.3. Indication of any immediate medical attention and special treatment needed, 6.1. Personal precautions, protective equipment and emergency procedures, 7.1. Precautions for safe handling, 7.3. Specific end use(s), 8.1. Control parameters, 8.2. Exposure controls, 10.1. Reactivity, 10.5. Incompatible materials, 11.1. Information on toxicological effects, 12.1. Toxicity, 12.2. Persistence and degradability, 12.5. Results of PBT and vPvB assessment, 12.6. Other adverse effects, 14.6. Special precautions for user, 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

- H220 = Extremely flammable gas.
- H280 = Contains gas under pressure; may explode if heated.
- H315 = Causes skin irritation.
- H318 = Causes serious eye damage.
- H330 = Fatal if inhaled.
- H225 = Highly flammable liquid and vapour.
- H319 = Causes serious eye irritation.
- H314 = Causes severe skin burns and eye damage.
- H335 = May cause respiratory irritation.
- H400 = Very toxic to aquatic life.
- H411 = Toxic to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main regulatory references:

- EC Regulation 1907/2006 of the European Parliament (REACH) and subsequent updates
- EC Regulation 1272/2008 of the European Parliament (CLP) and subsequent updates
- EC Regulation 830/2015 of the European Parliament and subsequent updates
- EC Regulation 648/2004 of the European Parliament and subsequent updates

The data contained in the present Safety Information Sheet is based on our current knowledge and provides information regarding the safe management and handling of the product. The present document is not a Certificate of Analysis, nor a technical information sheet, nor does it constitute an agreement regarding the specifications of the product.

***This data sheet annuls and substitutes each previous version.