

012A290062A - STOVILMATIC LIQUIDO

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 012A290062A
Product name: STOVILMATIC LIQUIDO
UFI : 0S62-C098-U00H-HQ0Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Automatic dishwashing detergent

Identified Uses	Industrial	Professional	Consumer
Automatic dishwashing detergent	-	✓	-
Uses Advised Against			
Do not use for uses other than those indicated			

1.3. Details of the supplier of the safety data sheet

Name: ALLEGRINI S.P.A.
Full address: Vicolo Salvo D'Acquisto, 2
District and Country: 24050 Grassobbio (BG)
Italy
Tel.: +39 035 4242111
Fax: +39 035 526588
e-mail address of the competent person responsible for the Safety Data Sheet: msds@allegrini.com

1.4. Emergency telephone number

For urgent inquiries refer to: Allegrini SpA : Tel. +39 035 4242111 Mon - Fri 8.00 - 17.00 GMT +1

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Substance or mixture corrosive to metals, category 1	H290	May be corrosive to metals.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

012A290062A - STOVILMATIC LIQUIDO

SECTION 2. Hazards identification ... / >>

Hazard statements:

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements:

P260 Do not breathe dust / fume / gas / mist / vapors / spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353 IN CASE OF CONTACT WITH SKIN (or hair): immediately take off all contaminated clothing. Rinse the skin [or take a shower].
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor.
P264 Wash your hands thoroughly after use.

Contains: Sodium hydroxide
Tetrasodium ethylene diamine tetraacetate

Ingredients according to Regulation (EC) No. 648/2004

Less than 5% Phosphonates
5% or over but less than 15% EDTA

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Sodium hydroxide		
INDEX	011-002-00-6	Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318 Skin Corr. 1B H314: ≥ 2%, Skin Irrit. 2 H315: ≥ 0,5%, Eye Dam. 1 H318: ≥ 2%, Eye Irrit. 2 H319: ≥ 0,5%
EC	215-185-5	
CAS	1310-73-2	
REACH Reg.	01-2119457892-27	
Tetrasodium ethylene diamine tetraacetate		
INDEX	607-428-00-2	Acute Tox. 4 H302, Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318 LD50 Oral: 1780 mg/kg, STA Inhalation mists/powders: 1,5 mg/l
EC	200-573-9	
CAS	64-02-8	
REACH Reg.	01-2119486762-27	
Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate		
INDEX	257-573-7	Met. Corr. 1 H290
EC	51981-21-6	
CAS	51981-21-6	
REACH Reg.	01-2119493601-38	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

012A290062A - STOVILMATIC LIQUIDO

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

012A290062A - STOVILMATIC LIQUIDO

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2022

Tetrasodium ethylene diamine tetraacetate

Predicted no-effect concentration - PNEC

Normal value in fresh water	2,2	mg/l
Normal value in marine water	0,22	mg/l
Normal value for water, intermittent release	1,2	mg/l
Normal value of STP microorganisms	43	mg/l
Normal value for the terrestrial compartment	0,72	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 mg/kg				
Inhalation	1,2 mg/m3			0,6 mg/m3	3 mg/m3			1,5 mg/m3

012A290062A - STOVILMATIC LIQUIDO

SECTION 8. Exposure controls/personal protection ... / >>

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,45	mg/l
Normal value in marine water	0,945	mg/l
Normal value for water, intermittent release	0,953	mg/l
Normal value of STP microorganisms	41,2	mg/l

Sodium hydroxide

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
TLV	BGR	2				
TLV	CZE	1		2		
VLA	ESP			2		
VLEP	FRA	2				
TLV	GRC	2		2		
AK	HUN	1		2		
GVI/KGVI	HRV			2		
NDS/NDSch	POL	0,5		1		
NPEL	SVK	2				
MV	SVN	2		2		INHAL
WEL	GBR			2		
TLV-ACGIH				2 (C)		

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			1 mg/m3				1 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

012A290062A - STOVILMATIC LIQUIDO

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellow	
Odour	odourless	
Melting point / freezing point	< 0 °C	
Initial boiling point	100 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 70 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	13	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,245	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Sodium hydroxide

Exorma reaction with water. Reaction with acids and with alkaline-terrosis metals. It reacts with aluminum or its alloys in the presence of water to form hydrogen.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

Avoid overheating and contact with incompatible materials.

Sodium hydroxide

Avoid exposure to: air,moisture,sources of heat.

10.5. Incompatible materials

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

Avoid contact with: strong acids,strong oxidising agents,strong bases.

012A290062A - STOVILMATIC LIQUIDO

SECTION 10. Stability and reactivity ... / >>

Sodium hydroxide

Incompatible with: strong acids, ammonia, zinc, lead, aluminium, water, flammable liquids.

Aluminium and light alloys.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:

> 5 mg/l

ATE (Oral) of the mixture:

>2000 mg/kg

ATE (Dermal) of the mixture:

Not classified (no significant component)

Tetrasodium ethylene diamine tetraacetate

LD50 (Oral):

1780 mg/kg Rat

LC50 (Inhalation vapours):

> 1 mg/l/4h Rat

STA (Inhalation mists/powders):

1,5 mg/l

(figure used for calculation of the acute toxicity estimate of the mixture)

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

LD50 (Dermal):

> 2000 mg/kg Rat

LD50 (Oral):

> 2000 mg/kg Rat

Sodium hydroxide

LD50 (Oral):

> 2000 mg/kg rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

012A290062A - STOVILMATIC LIQUIDO

SECTION 11. Toxicological information ... / >>

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Tetrasodium ethylene diamine tetraacetate

NOAEL: F1: > 250 mg/kg (Rat)

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Tetrasodium ethylene diamine tetraacetate

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	140 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 25,7 mg/l (35d)
Chronic NOEC for Crustacea	> 25 mg/l (21d)

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

LC50 - for Fish	95,26 mg/l/96h
EC50 - for Crustacea	25,26 mg/l/48h

Sodium hydroxide

LC50 - for Fish	> 35 mg/l/96h
EC50 - for Crustacea	40,4 mg/l/48h Daphnia

12.2. Persistence and degradability

Tetrasodium ethylene diamine tetraacetate

NOT rapidly degradable

Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate

Rapidly degradable

Sodium hydroxide

Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

012A290062A - STOVILMATIC LIQUIDO**SECTION 12. Ecological information** ... / >>

Information not available

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1719

14.2. UN proper shipping name

ADR / RID: CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Hydroxide; Ethylenediaminetetraaceticacid na4 - salt)

IMDG: CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Hydroxide; Ethylenediaminetetraaceticacid na4 - salt)

IATA: CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Hydroxide; Ethylenediaminetetraaceticacid na4 - salt)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

012A290062A - STOVILMATIC LIQUIDO

SECTION 16. Other information ... / >>

H302	Harmful if swallowed.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website

012A290062A - STOVILMATIC LIQUIDO

SECTION 16. Other information ... / >>

- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

09.